

E2200



Industrial Combustion Analyzer

Providing the latest in Combustion Gas & Emissions Analyzers for Boiler, Engine, Furnace, and other Combustion Applications

- NO/NO_x Sensor Included
- CO Sensor w/ NO_x Filter
- Built-In NON-THERMAL Printer
- Draft & Differential Pressure Meter
- 2 Channel Thermometer
- Ambient CO & NO Monitor
- ONE Button Operation
- CO with 1 ppm Resolution
- Rechargeable Batteries
- ZOOM Function
- Immediate Response Time
- External Condensation Trap
- 600 Test Internal Memory
- PC Software Included



O₂

CO₂

CO

NO

NO_x

Efficiency

Excess Air

Tair Tgas

DRAFT

Diff. Press

Ambient
CO & NO



**Unbreakable Metal
Probe Connections**



**Field Replaceable
Pre-Calibrated Sensors**

E Instruments International

www.E-Inst.com

P: 215-750-1212 F: 215-750-1399 A: 172 Middletown Blvd, Ste B201 Langhorne, PA 19047

E2200 Features

Internal Impact Printer

A built-in impact printer uses **NON-THERMAL** paper rolls for easy printing of data without extra parts or communications needed.



Pre-Calibrated Gas Sensors

The field-replaceable, pre-calibrated gas sensors can easily be replaced in the field to provide a convenient way to minimize costly downtime!

BIG Bright BLUE Backlight w/ ZOOM Feature



Magnetic Rubber Boot "Hands-Free"

Unbreakable Metal Connections



Durable "Boiler Room" Design

10' Dual Hose, 12" Probe
Gas, Draft, Temp = All-at-once

10 Fuel / Oil Types
Including **Bio-Heat 5%**



Parameter	Sensor	Range	Resolution	Accuracy
O ₂	Electrochemical	0 - 25%	0.1%	±0.2% vol
CO	Electrochemical	0 - 8000 ppm	1 ppm	±20 ppm <400ppm ±5% rdg up to 2000 ppm ±10% rdg for >2000 ppm
H ₂ Compensated w/ Built-in NO _x Filter				
CO ₂	Calculated	0 - 99.9%	0.1%	
NO	Electrochemical	0 - 4000 ppm	1 ppm	±5 ppm <100ppm ±5% rdg up to 1000 ppm ±10% rdg for >4000 ppm
NO _x	Calculated	0 - 5000 ppm	1 ppm	
Tair	Pt100	-10 to 212°F	0.1°F	± 1°F
Tgas	Tc K	-10 to 1830°F	0.1°F	± 2°F
Differential Temp.	Calculated	-10 to 1830°F	0.1°F	
Pressure/Draft	Semiconductor	± 0 - 40 inH ₂ O	0.001 inH ₂ O	±0.008 inH ₂ O for ±0.16 inH ₂ O ± 5% meas. val. elsewhere
Excess Air	Calculated	1.00 - infinity	0.01	
Efficiency	Calculated	0-100%	0.1% (also for condensing boilers with automatic detection)	

Ordering Information

Model No.	Description
E2200-1	E2200 Unit (O ₂ , CO, CO ₂ , NO/NO _x , Efficiency, Excess Air, Draft, Pressure, Temp, Rechargeable Battery & AC Plug, Hose, Probe, Hard ABS Case, Calibration Certificate, Operating Manual, Water Trap, Paper Roll, Memory, PC Software & Built-In Printer Included!)



Pre-Calibrated Gas Sensors



Unbreakable Metal Connections



E2200-1