



# Gas Sniffer Model 7899



## Combustible Gas Leak Detector

- Auto Zero-Drift Adjustment
- Visual and Audible Alarms
- LCD and Bar Graph Display

|                        |   |
|------------------------|---|
| Batteries:             | 9V, 6x1,6V AAA  |
| External power supply: | 120/240V 12V 100mA (optional)                           |
| Battery life:          | 4 hours minimum   |
| Measurement range:     | 0.0 - 10,000 ppm CH <sub>4</sub>                        |
|                        | 0.0 - 1% VOL CH <sub>4</sub>                            |
|                        | 0.0 - 20% LEL CH <sub>4</sub>                           |
|                        | 0.0 - 1,800ppm LPG (isoC <sub>4</sub> H <sub>10</sub> ) |
| Resolution:            | 1 ppm   |
| Accuracy:              | ± 20% f.s. @ 20°C ± 1°C                                 |
| Measurement units:     | ppm, %vol, %L.E.L.                                      |
| Sensor type:           | Semiconductor   |
| Pre-heating time:      | Max. 45 seconds fixed                                   |
| Auto-shut-off time:    | OFF, 1 - 30 minutes                                     |
| Display:               | LCD TN  |
| Operating temperature: | 32° to 104°F (0° to 40°C)                               |
| Storage temperature:   | 14° to 122°F (-10° to +50°C)                            |
| Humidity limits:       | 20% - 80% RH non condensating                           |
| Enclosure:             | ABS HB self-extinguishing                               |
| Dimensions:            | 2.8" x 6" x 1.5" (W x H x D)                            |
| Weight:                | 0.7 lbs. (0.3 kg)                                       |
| Flexible Probe Length: | 11" (270 mm)  |



**E Instruments International**

P:215-750-1212 F:215-750-1399 A: 172 Middletown Blvd, Ste B201 Langhorne, PA 19047

**www.E-Inst.com**